

FIRE EXTINGUISHER

ABGStored Pressure Type Fire Extinguisher



Suitable for all types of Fires Pape, Wood, cloth, Plastic & Solid combustible material, Petrol,Oil, Paints Sprits, Chemicals, Cooking & Welding Gas fire & Sophisticated Electricals, Electronics Equipment & Computer Fires etc.



Extinguishing Agent	Co ₂ gas blanketing					
Available capaciy in kgs	2	3	4.5	6.5	9	22.5
IS Specification	2078					
Jet range in mts	2	2	2.5	2.8	3.5	4
Discharge time in sec's	14-15	16-10	20-24	25-30	25-35	50-60

Suitable Fire Fighting All flammable liquid Gases, Live & Delicae Machinery fire, Electrical & sophisticated Electronics Equipment fires etc.

Water Cooling

Extinguishing agent	Water Cooling				
available capacity in Itrs	9	45	150		
IS Specification	940	13385	13385		
Jet range in mts	5	10	20		
Discharge time in sec's	8-120	60-180	60-180		

DO NOT USE ON ELECTRICAL FIRES Suitable for fire fighting of Wood, Paper, Cotton, Jute etc.

Mechanical Foam

E				
Extinguishing agent	Mechanical Foam			
Available capacity in ltrs	9	45	150	
IS Specification	10204	13386	13385	
Jet range in mts	5	10	20	
Discharge time in sec's	8-120	60-180	60-180	

Suitable for Fire Fighting of Paints, Spirit, Chemicals, flammable liquids fires etc.

DO NOT USE ON ELECTRICAL FIRES

Dry Chemical Powder type Extinguisher

Extinguishing Agent	Dry Powder Blanketing					
Available capaciy in kgs	1,2	5	10	25	50	75
IS Specification	2171 10658					
Jet range in mts	2	4.5	6	6	6	10
Discharge time in sec's	8-10	15-20	23-30	25-30	40-50	50-60

Suitable Fire Fighting of Oil, Solvents, Gases, Paints, Varnish, Electrical Wiring, Live Machinery fire Cotton, Jute etc. All flammable Liquid & Gas fires etc.







Pro Safety fire wheeled extinguishers are available in ABC Powder and ofer exceptional value for moneyu as well as the highquality that you would expect from Pro Safety fire fighting products. Pro Safety wheeled extinguishers are ideal for use in a wide range of commercial and industrial appliations.



Automatic fire extinguishers are ideal for use in unoccupied rooms or areas and can be used to provide fire saety protection in an enclosed space.



Fire Extinguisher Type : A B C Dry Powder Type

Capacity : 4.5Kg, 5Kg
Fire Class : A, B, C
Weight : 10-12 kg
Discharge Time : 20 seconds
Working Pressure : 12 Bar



FIRE DETECTION



Addressable Fire Alaram Panel

250 device detectors and modules in each loop 64/128/512 completely programmable Softare zones 16 programmable open-collector Outputs RS485 Interface for the connection of up to 8 FC200/REP Repeaters and up to 8 panels



Response Indicators

Maximum volt.: 24volt.

Addressable Fire Alaram Panel

EN54 approved by LPCB Low operational voltage: 10.5V to 33V Integrated alarm led Remote led connection Compatible with standard mounting base and with relay base





Manual Call Point

Maximum volt. :24volt. Maximum Current:4 amps

Hooter

Maximum volt. : 12/24volt.

Maximum Current : 4 amps

Sound Levels : 90-120/db



Fire Alarm Panel



Fire Alarm System is designed to alert us to an emergency so that we can take action to protect ourselves, staff and the general public.

Fire alarms are found in Offices, Factories, and public buildings, they are a part of our everyday routine but are often overlooked until there is an emergency at which point, they might just save our lives.

Whatever the method of detection is, if the alarm is triggered, sounders will operate to warn people in the building that there may be a fire and to evacuate.

The fire alarm system may also incorporate a remote signal system which could then alert the fire brigade via a central station.

So what is a fire alarm system, or fire detection system? In this article, we will have a look at the structure and types of the "Fire Alarm Systems".

Conventional Fire Alaram Panel

Networkable Model – Monitor from Anywhere! Fire LINX software for Monitoring, Control and

data collection 90 – 270V AC, 50Hz , 30W SMPS Independent Relays for Fire &

Fault Rugged construction with powder coated finish



SAFETY PRODUCTS



HYDRANT SYSTEM

PUMP HOUSE GALLERY

SINGLE HEAD HYDRANT VALVE

ISI -5290-A
Oblique type inlet
Mounted on stand post
Painted natural red
Blank cap
Bronze material



FIRST AND HOSE REEL

Swinging wall mounting type Complete with 36O revolving 30 mts long high pressure hose 6mm shut off nozzle / PVC As per IS 444 type



CP HOSE

Control percolating hose Made from synthetic fiber Circular woven jacketed Heat resistance 15mts length Female and male coupling



HOSE BOX

Made with sheet hose box M.S. Steel hinges door handle Size "46x32x10" Glass window and keys



BRANCH PIPE

Made with Bronze 2½ male coupling As per IS 903 Branch Outlet 12mm



SPRINKLER FLEXIBLE FIRE SPRINKLER

Automatic fire sprinklers Quartz build Operate a predetermined temperature Ceiling Sprinklers & wall mounting Sprinklers.







THE STATE OF THE S

Alarm System



Delivery Output & Drain



Negative Pressure fire pump House



Butterfly valves fittings



Negative Pressure Portable Fire Pump House



Hydrant Wet Raiser



Positive Pressure Fire Pump House



Portable pump House



Hose hox, Hose reel drums & fittings



Fire Brigade Connection



2way inlet

Inlet Breeching S.G.I Body having 02 gunmetal 63mm male instantaneous inlets conforming to IS:903, fitted with nonreturnvalves, flange outlet 220mm OD, 180mm PCD, eight holes Of 19mm dia complete with 02 PVC blank caps andChains

OUR MAJOR CLIENTS



Infra Sector



















RVR Towers

Fortune Towers

Varsha Building (P) Ltd. Varun Towers

Pharma Sector



































Bio-Tech Sector











Emmennar Bio-tech

Hospital Sector













VB Chest Hospital

Govt. Hospitals (VJA-NZD-GNT & MTM)

Hotel Sector













Innotel Vijayawada

Distillary Sector



TGV SRAAC Ltd.

SPY AGRO

Schools & Colleges Sector























State & Central Govt. Sectors









Conventional Centre Sectors





Other Sectors











Film Studio Sector





Autmobile

Sai Services

Varun Group















SRI SARADHI

FIRE SAFETY SYSTEMS

ISO 9001-2015 CERTIFIED COMPANY

All Types of Fire Equipments, ISI Marked (Govt. Regd.)

Govt. & Semi Govt. Suppliers, Fire Hydrant Systems, Sprinkles Systems
Fire Alaram, Fire Extinguishers, Refilling and Servicing Contractors & Safety Equipments etc.

Plot No. 20, CPR Colony, Venkateshwara Nagar, Nr. Mazid, Qutubullapur, Hyderabad -500 054.

E-mail | linfo@srisaradhiffre.com

website | www.srisaradhiffre.com

Telefax: 040-23084034 Cell: 91 9948456219, 91 8328422800